

FLOOR TYPE FANCOIL

فن کوئل زمینی



The rule of judging tubing's direction

Facing air, if the tubing on the left, it is left style, contrarily, it is right units with 1 coil (2-pipes system)

UNITS WITH 1 COIL (2-PIPES SYSTEM)												
Model			AF 032(L/R)SF	AF 052(L/R)SF	AF 062(L/R)SF	AF 072(L/R)SF	AF 082(L/R)SF	AF 102(L/R)SF	AF 122(L/R)SF	AF 142(L/R)SF	AF 162(L/R)SF	AF 202(L/R)SF
Cooling capacity	total	kW	2.06	2.98	3.5	4.02	4.5	5.31	6.07	7.46	8.61	10.61
	sensible	kW	1.69	2.41	2.73	3.23	3.51	4.25	5.36	5.93	6.76	8.6
Heating capacity (1*)		kW	3.403	5.299	5.763	6.372	7.012	8.211	11.295	12.112	15.507	17.292
heating capacity (2*)		kW	4.084	6.359	6.916	7.646	8.376	11.053	13.554	14.534	19.704	20.75
Air flow	CFM		252	364	395	470	501	622	671	910	1166	1324
	m ³ /h		428	619	671	813	888	1058	1480	1560	1998	2250
Cooling water flow		l/h	365	520	600	699	760	930	1230	1333	1500	1840
Heating water flow		l/h	383	571	650	777	836	995	1305	1385	1619	2052
Water essure drop	cooling	kpa	12.3	9.3	12.4	16.6	21.6	32.5	32.5	20.5	28.2	44.5
	heating	kpa	14.3	10.5	13.6	18.5	22.6	33.8	33.8	22.2	29.2	45.4
Sound level db (A)	max		34	36	37	39	43	44	44	46	47	49
	med		29	29	29	32	37	39	39	41	42	45
	min		23	24	24	27	29	30	32	32	32	34
Dimension	L	mm	908	950	1058	1108	1208	1308	1408	1608	1608	1908
	W	mm	235	235	235	235	235	235	235	235	235	235
	H	mm	483	483	483	483	483	483	483	483	483	483
Input		W	32	42	55	72	80	91	125	151	161	168

1* : Heat water input temperature: t=60°C, water outlet temperature : t=50°C, difference:t=10°C

2* : Heat water input temperature: t=70°C, the same water flow as 1*

apratrad@apratrading.com

TEI : +982188318805

Fax: +982188318806